CNCGLASS
CNC Ucolin Interlayer Technology Co., Ltd.
SHENZHEN, GD, CHINA
Peter Lin · cnc@cncglass.com · WhatsApp / Mobile +86 15013829504
WeChat wecan365 · www.cncglass.com

Thin-Film Photovoltaics and the Encapsulant Questions They Raise

A different cell, not a world without encapsulants

Thin-film photovoltaic modules deposit the semiconductor as a coating on glass or on a flexible foil, rather than wiring a wafer into the stack. Cadmium telluride, copper indium gallium selenide, and amorphous or tandem silicon stacks are the familiar industrial families, with newer coatings still moving from the laboratory toward production. The module that leaves the factory is still a sealed package. Glass, edge seals, and, in many constructions, a polymer encapsulant or backsheet system still decide whether that coating survives heat, humidity, and handling.



Figure 1. Encapsulant film remains part of many thin-film packages, even when the cell is not a wafer.

This is why an interlayer company pays attention to thin film. The cell may be thinner; the need for a dry, electrically quiet, optically useful package is not.

Where the package differs from a crystalline module

Many thin-film devices are grown on the front glass, so the “lay-up” is not two EVA sheets around a wafer string. Some designs use a second glass with an edge seal, some use a polymer backsheet, and some still use a sheet encapsulant to bond and cushion the structure. Moisture sensitivity can be higher than in a well-built crystalline module, which is why edge-seal quality and, where a polymer is used, barrier behavior receive so much attention.

Process temperatures and chemical compatibility also change. A film or seal that is routine on a wafer line may be wrong for a coating that dislikes a particular additive or a particular lamination temperature. Qualification has to be done on the real stack.



Figure 2. Optical-grade rolls used when a thin-film stack still relies on a polymer seal.

Installation changes that follow the module

Thin-film modules are often lighter and, in some flexible forms, able to follow a curved or a low-load surface. Building-integrated and large-area glazed installations have used that freedom. The electrical and mechanical design still has to respect the package: bending limits, cable entries, and the same dislike of standing water at the edge that every sealed module has.

We do not present thin film as a universal replacement for crystalline silicon, or the other way around. Each has a place, and each is only as good as the seal that keeps the semiconductor in a stable climate.



Figure 3. Process film on a line: thin-film factories are as sensitive to moisture and lamination as wafer lines.

What we offer to this conversation

Where a thin-film design still uses an EVA, POE, or related sheet, the usual discipline applies: dry storage, a documented cycle, and optics and resistivity that match the device. Where the design is glass-glass with an edge seal and little or no sheet encapsulant, our role may be limited to a related interlayer or to a frank statement that the package is not an EVA problem.

That honesty is part of being useful. Thin-film installation is changing solar practice; it should not change the habit of specifying the package with care.

Thin-film modules change how the semiconductor is made. They do not remove the need for a dry, stable, well-specified package. When a polymer encapsulant is part of that package, it should be chosen with the same seriousness as in crystalline work.

Contact Us

Brand: CNCGLASS

Company: CNC Ucolin Interlayer Technology Co., Ltd.
Address: SHENZHEN, GD, CHINA
Contact: Peter Lin
Email: cnc@cncglass.com
WhatsApp / Mobile: +86 15013829504
WeChat: wecan365
Website: www.cncglass.com

If your thin-film design uses a sheet encapsulant, we can help qualify EVA or POE against the coating, the glass, and the cycle.